
File Edit View Player Tools Help
Search
Playing Now
Audio
Images
Video
Television
Cloudplay
Streaming
Action
Burn Disc
Rip Disc
Sync Handl
Camera
Build Playli
Tag
Options
Audio
Burning
CD, DVD & BD
Cloudplay
Encoding
Zone to configure:
Player
Audio Device
exaSound ASIO64 (2ch) [ASIO]
Device settings...
Settings
DSP & output format...
DSP Studio
Output Format
Volume Leveling
Adaptive Volume
Equalizer
Parametric Equalizer
Effects
Headphones
Tempo & Pitch
Room Correction
Convolution
Parametric Equalizer 2
Analyzer
Processed in order listed (drag to reorder)
Manage Plug-ins...
Clip protection
Output Format
Playback stopped or current playback doesn't support processing
Options
Sound can be output in any format. For example, you can listen to an audio CD in 5.1 surround at 32-bit / 192 kHz. Advanced settings like multi-channel output or high sample rates require a sound card capable of these modes.
Output Encoding (more info)
8xDSD in native format (requires ASIO and 8xDSD capable DAC)
Sample rate (more info)
Click in the output column to select a sample rate for each input sample rate. Right-click to set all at once.
Input
Output
Less than 44,100 Hz
44,100 Hz
48,000 Hz
88,200 Hz
96,000 Hz
176,400 Hz
192,000 Hz
352,800 Hz
384,000 Hz
705,600 Hz
No change
Channels (more info)
Channels: 2 channels (stereo)
Center: 0 dB
Mixing: JRSS™ mixing (recommended)
For stereo sources, only mix to 2.1
Move center to front L/R
Detect stereo sources in surround (pseudo-surround)
Subwoofer (more info)
When source has no subwoofer (Stereo, etc.) and 'Channels' selection includes a subwoofer, or subwoofer is being downmixed:
JRSS Subwoofer (120 Hz low-pass)
Subclarity™ for cleaner, tighter subwoofer output